

A



B

C


D

E

F



M 1:5 (Ø150)



WGR	MAT
2R2	1.4301(304)-2R(IIID)
2B2	1.4301(304)-2B(IIIC)
2J2	1.4301(304)-2J(GEB)FO

Ø	060	080	090	100	110	115	120	125	130	140	145	150	160	165	170	175	180	185	190	195	200
B	60	81	91	101	111	116	121	126	131	141	146	152	161	166	171	176	181	186	191	196	201
C	170																				
D	240																				
kg	1,44	1,52	1,52	1,53	1,54	1,55		1,56	1,57	1,76		1,77	1,78	1,79		1,8		1,87		1,88	
Ø	205	210	215	220	225	230	235	240	245	250	255	260	265	275	280	285	290	295	300		
B	206	211	216	221	226	231	236	241	246	251	256	261	266	276	284	286	291	296	301		
C	170																				
D	240																				
kg	1,89		1,92		1,93	1,94		1,95	1,97	1,98	1,99		2,07	2,08	2,09		2,1		2,11		

notes:

DIN ISO 13920 Tolerances B

revisions-no.

A00

mm / kg

date

name

drawn by

23.02.22

MSA

checked by

23.02.22

SWA

approved by

23.02.22

JWY

modified by

Jeremias[®]
CHIMNEY SYSTEMS

description Wall bracket adjustable, wall distance 250-360mm

code **WGR-ZUAC24Ø**

drawing-no. **07-04-0223-000**

scale

1:5

format

A4

sheet

1 of 2



